



Expert tips

Connection options M22–M24

Until the end of 2008, the DYNAJET machines within the 500 bar (7.250 PSI) pressure range were supplied with M22 x 1.5 connections and extension pipes with a diameter of 1/4" .

Since the start of 2009, however, all DYNAJET machines within the 500 bar (7.250 PSI) pressure range are now supplied as standard with pressure outlets, quick-release couplings, etc. in a M24 x 1.5 version and with extension pipes with a diameter of 3/8" .

The overview to the right includes the options for joining and coupling the M22 x 1.5 connections to the current M24 x 1.5 size.

M22 x 1,5 IT	Adapter M22 ET - M22 ET Part no. 427 518	M22 x 1,5 IT
		
M24 x 1,5 IT	Adapter M24 ET - M24 ET Part no. 502 954	M24 x 1,5 IT
		
M22 x 1,5 IT	Adapter M22 ET - M24 ET Part no. 532 938	M24 x 1,5 IT
		
M22 x 1,5 IT	Adapter M22 ET - M24 IT Part no. 532 939	M24 x 1,5 ET
 		
M24 x 1,5 IT	Adapter M24 ET - M22 IT Part no. 532 940	M22 x 1,5 ET
 		
M24 x 1,5 IT	Adapter M24 IT - M22 IT	M22 x 1,5 ET
	 M24 IT Part no. 502 975 M22 IT Part no. 427 585	